



SAFETY DATA SHEET

GRAVIS SP 460

Prepared according to Annex II of EC regulation 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME GRAVIS SP 460
SUPPLIER OMV PETROL OFİSİ A.Ş.
Ayazağa Eski Büyükdere Cad.
No:33-37 B Blok 34398
Maslak-Istanbul/TURKEY
Tel: +90 212 329 1500
Fax: +90 212 329 1896
www.poas.com.tr
info@poas.com.tr
PRODUCT NO. 28134
APPLICATION Industrial oil
EMERGENCY TELEPHONE POAŞ: +90 212 329 1845 (office hours)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Alkyl phosphate			< 1%	C;R34.
Alkyl phosphonate			< 1%	Xi;R41,R38. N;R51/53.
Long chain alkenyl amine			< 1%	Xn;R22. C;R35. N;R50.
Long chain alkyl amine			< 1%	T;R23/24. Xn;R22,R48/20. C;R34. N;R50/53. R43.
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.; KEROSENE - UNSPECIFIED	265-198-5	64742-94-5	< 1%	Xn;R65

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

INGESTION

Do not induce vomiting. Remove victim immediately from source of exposure. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Carbon dioxide (CO2). Foam. Dry chemicals. Water spray.

GRAVIS SP 460

UNUSUAL FIRE & EXPLOSION HAZARDS

Avoid breathing fire vapours. Ventilate closed spaces before entering them.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container. Keep away from food, drink and animal feeding stuffs.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Yellow		
ODOUR	Characteristic.		
RELATIVE DENSITY	0,86 g/ml 15	VISCOSITY	472,4 cSt 40
FLASH POINT (°C)	258 OC (Open cup).		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

MATERIALS TO AVOID

Strong oxidising substances.

GRAVIS SP 460

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Skin irritation is not anticipated when used normally.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

DEGRADABILITY

The degradability of the product has not been stated.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

ROAD TRANSPORT NOTES

Not Classified

RAIL TRANSPORT NOTES

Not classified.

SEA TRANSPORT NOTES

Not classified.

AIR TRANSPORT NOTES

Not classified.

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

P14 Contains Long chain alkyl amine. May produce an allergic reaction.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

INFORMATION SOURCES

This SDS is prepared based on the information received from raw material suppliers.

ISSUED BY

Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)

DATE

21.06.2011

GRAVIS SP 460

RISK PHRASES IN FULL

R34	Causes burns.
R35	Causes severe burns.
R22	Harmful if swallowed.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R41	Risk of serious damage to eyes.
R23/24	Toxic by inhalation and in contact with skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50	Very toxic to aquatic organisms.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.