



SAFETY DATA SHEET

ROCK DRILL LUBRICANT 100

Prepared according to Annex II of EC regulation 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME ROCK DRILL LUBRICANT 100

SUPPLIER OMV PETROL OFİSİ A.Ş.
Ayazağa Eski Büyükdere Cad.
No:33-37 B Blok 34398
Maslak-Istanbul/TURKEY
Tel: +90 212 329 1500
Fax: +90 212 329 1896
www.poas.com.tr
info@poas.com.tr

PRODUCT NO. 29132

APPLICATION Industrial oil

EMERGENCY TELEPHONE POAŞ: +90 212 329 1845 (office hours)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

ENVIRONMENT

The product is not expected to be hazardous to the environment.

HUMAN HEALTH

Prolonged skin contact may cause temporary irritation. Splashes in the eyes may cause redness and irritation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Alkyl phosphate			< 1%	C;R34.
Long chain alkenyl amine			< 1%	Xn;R22. C;R35. N;R50.
Long chain alkyl amine			< 1%	T;R23/24. Xn;R22,R48/20. C;R34. N;R50/53. R43.
Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)	278-012-2	74869-22-0	60-100%	-

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Some substances are not classified by legislation.They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

ROCK DRILL LUBRICANT 100

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Yellow		
RELATIVE DENSITY	0,89 g/ml 15	VISCOSITY	106.9 cSt 100
FLASH POINT (°C)	222 OC (Open cup).		

ROCK DRILL LUBRICANT 100

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidisers.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Liquid may irritate skin.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

ROAD TRANSPORT NOTES

Not Classified

RAIL TRANSPORT NOTES

Not classified.

SEA TRANSPORT NOTES

Not classified.

AIR TRANSPORT NOTES

Not classified.

15 REGULATORY INFORMATION

RISK PHRASES

NC

Not classified.

SAFETY PHRASES

P14

Contains Long chain alkyl amine. May produce an allergic reaction.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION COMMENTS

Company name changed

ISSUED BY

Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)

ROCK DRILL LUBRICANT 100

REVISION DATE 16.06.2011

DATE 15.09.2010

RISK PHRASES IN FULL

NC	Not classified.
R22	Harmful if swallowed.
R23/24	Toxic by inhalation and in contact with skin.
R34	Causes burns.
R35	Causes severe burns.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50	Very toxic to aquatic organisms.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.