



# SAFETY DATA SHEET

## MAXIMUS SUPER DIESEL 20W-50

Prepared according to Annex II of EC regulation 1907/2006

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**PRODUCT NAME** MAXIMUS SUPER DIESEL 20W-50

**SUPPLIER** OMV PETROL OFİSİ A.Ş.  
Ayazağa Eski Büyükdere Cad.  
No:33-37 B Blok 34398  
Maslak-Istanbul/TURKEY  
Tel: +90 212 329 1500  
Fax: +90 212 329 1896  
www.poas.com.tr  
info@poas.com.tr

**PRODUCT NO.** 11345

**APPLICATION** Engine oil

**EMERGENCY TELEPHONE** POAŞ: +90 212 329 1845 (office hours)

### 2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name                                                                                                          | EC No.    | CAS-No.    | Content | Classification (67/548)             |
|---------------------------------------------------------------------------------------------------------------|-----------|------------|---------|-------------------------------------|
| Alkoxylated long chain alkyl alcohol                                                                          |           |            | < 1%    | Xi;R41. N;R50.                      |
| Calcium long chain alkaryl sulfonate                                                                          |           |            | < 1%    | Xi;R38.                             |
| Calcium long chain alkylphenate sulfide                                                                       |           |            | < 1%    | R53.                                |
| Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50) | 278-012-2 | 74869-22-0 | 70-90%  | -                                   |
| Phenol 4-dodecyl                                                                                              |           | 104-43-8   | < 1%    | Repr. Cat. 3;R62. Xi;R38. N;R50/53. |
| Zinc alkyldithiophosphate                                                                                     | 272-028-3 | 68649-42-3 | 1-5%    | Xi;R38,R41. N;R51/53.               |

The Full Text for all R-Phrases are Displayed in Section 16

### COMPOSITION COMMENTS

Some substances are not classified by legislation.They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

Get medical attention if any discomfort continues.

#### NOTES TO THE PHYSICIAN

No specific treatment.treat symptomatically.

#### INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

#### INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

# MAXIMUS SUPER DIESEL 20W-50

## SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

## EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## 5 FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

This product is not flammable. Fire can be extinguished using: Foam, carbon dioxide or dry powder.

### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Keep run-off water out of sewers and water sources. Dike for water control.

### SPECIFIC HAZARDS

In case of fire, toxic gases may be formed (COx, NOx).

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

### HAND PROTECTION

Use suitable protective gloves if risk of skin contact. Use protective gloves made of: Nitrile. Polyvinyl chloride (PVC).

### EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

# MAXIMUS SUPER DIESEL 20W-50

|                         |                    |                  |              |
|-------------------------|--------------------|------------------|--------------|
| <b>APPEARANCE</b>       | Liquid             |                  |              |
| <b>COLOUR</b>           | Brown              |                  |              |
| <b>RELATIVE DENSITY</b> | 0.89 g/ml 15       | <b>VISCOSITY</b> | 20.1 cSt 100 |
| <b>FLASH POINT (°C)</b> | 238 OC (Open cup). |                  |              |

## 10 STABILITY AND REACTIVITY

**STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidisers.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

## 11 TOXICOLOGICAL INFORMATION

**INHALATION**

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Liquid may irritate skin.

**EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

## 12 ECOLOGICAL INFORMATION

**ECOTOXICITY**

Not regarded as dangerous for the environment.

## 13 DISPOSAL CONSIDERATIONS

**GENERAL INFORMATION**

The packaging must be empty (drop-free, when inverted)

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Environmental manager must be informed of all major spillages. Do not allow runoff to sewer, waterway or ground.

## 14 TRANSPORT INFORMATION

|                             |                                                                                                                   |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>GENERAL</b>              | The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID). |
|                             | No transport warning sign required.                                                                               |
| <b>ROAD TRANSPORT NOTES</b> | Not Classified                                                                                                    |
| <b>RAIL TRANSPORT NOTES</b> | Not classified.                                                                                                   |
| <b>SEA TRANSPORT NOTES</b>  | Not classified.                                                                                                   |
| <b>AIR TRANSPORT NOTES</b>  | Not classified.                                                                                                   |

## 15 REGULATORY INFORMATION

**RISK PHRASES**

NC Not classified.

**SAFETY PHRASES**

P13 Safety data sheet available for professional user on request.

**STATUTORY INSTRUMENTS**

Chemicals (Hazard Information and Packaging) Regulations.

**APPROVED CODE OF PRACTICE**

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

# MAXIMUS SUPER DIESEL 20W-50

## GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

## 16 OTHER INFORMATION

### INFORMATION SOURCES

This SDS is prepared based on the information received from raw material suppliers.

### REVISION COMMENTS

Company name changed

### ISSUED BY

Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)

**REVISION DATE** 17.06.2011

**DATE** 30.03.2011

### RISK PHRASES IN FULL

|        |                                                                                                  |
|--------|--------------------------------------------------------------------------------------------------|
| NC     | Not classified.                                                                                  |
| R38    | Irritating to skin.                                                                              |
| R41    | Risk of serious damage to eyes.                                                                  |
| R50    | Very toxic to aquatic organisms.                                                                 |
| R50/53 | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.      |
| R53    | May cause long-term adverse effects in the aquatic environment.                                  |
| R62    | Possible risk of impaired fertility.                                                             |

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.