



Petrol Ofisi Hydraulic SAE 10W

High Performance Off-road Hydraulic Oil

Description

Petrol Ofisi Hydraulic SAE 10W is high performance hydraulic oil that is especially developed for construction machines hydraulic systems under heavy works. Provides longer equipment life by its high oxidation and corrosion resistance. It helps to extend the oil changing periods, provides economy from operative expenses.

Applications

Used in hydraulic systems of construction machines, heavy duty vehicles and agricultural machinery.

Benefits

- Prevents deposit accumulation, keeps the system clean.
- Extremely resistant against wear, oxidation, foaming.
- High viscosity index ensures easy start and compensates temperature differentiation.
- Sistemde oluşan nemin ve suyun pas yapmasını engeller.
- Perfectly compatible with leak tightness elements and standard seal materials.
- Extends the equipment life and reduces maintenance costs.

Performance

API CF, Allison C3, CAT TO-2

Typical Properties*		
SAE Viscosity Category		SAE 10W
Density, @ 15°C g/ml	ASTM 4052	0.882
Flash Point, COC, °C	ASTM D 92	228
Kinematic Viscosity	ASTM D 445	@ 40°C mm ² /s
		@ 100°C mm ² /s
Viscosity Index	ASTM D 2270	116
Pour Point, °C	ASTM D 97	-30

* Values may differ slightly between manufacturing parties.

